WELLS LAMONT

Industrial

Sizing:

PRODUCT SPECIFICATION SHEET

## **PRODUCT INFORMATION**

Style: Y9289

Size Part # Overedge

XSmall Y9289XS Yellow Small Red Y9289S Medium Y9289M Green Large Y9289L Brown XLarge Y9289XL Blue XXLarge Y9289XXL Black

Registered Brand Name: FlexTech™
Classification: Palm Dip



Description: Fully Coated with Palm & Finger Coating, Seamless Machine Knit

Color: Blue Shell / Black Palm

Shell: Synthetic Knit

Palm Coating: Full NBR Coating and Sandy Nitrile Palm Coating

Sold by: Dozen Pair Packaging (Inner Pack): 12 Pairs Packaging (Case Pack): 144 Pairs

## **CUT PROTECTION PERFORMANCE INFORMATION**

Test Method: ASTM F1790-97
Test Results: 267 grams / 0.59lbs.

ANSI Level 1

Test Method: ASTM F2992-15
Test Results: 286 grams
ANSI Level A1

Test Method: ASTM D3389-10

Test Results: ANSI Level 4 3,831 Cycles

**CE EN 388 STANDARD** 

ABRASION PROTECTION PERFORMANCE INFORMATION

 EN Abrasion Resistance:
 \$ 6.1
 Level 4

 EN Cut Resistance:
 \$ 6.2
 Level 1

 EN Tear Resistance:
 \$ 6.3
 Level 2

 EN Puncture Resistance:
 \$ 6.4
 Level 1

## WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pretreat with a stain remover. Do not use bleach or dry cleaning solution.

## **CAUTION**

This glove does not contain cut resistant materials. Do not use in conditions where cut protection is needed.

Wells Lamont Industrial

Toll-Free 1.800.247.3295 www.wellslamontindustrial.com

© 2019 Wells Lamont Industrial, LLC - All rights reserved.

KM 3/19