

**PRODUCT SPECIFICATION SHEET****PRODUCT INFORMATION**

<b>Style:</b>	<b>I2459</b>		
<b>Sizing:</b>	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	Small	I2459S	Red
	Medium	I2459M	Green
	Large	I2459L	Brown
	XLarge	I2459XL	Navy Blue
XXLarge	I2459XXL	Black	
<b>Registered Brand Name:</b>	FlexTech™		
<b>Classification:</b>	Impact		

**PRODUCT DESCRIPTION**

<b>Description:</b>	Seamless Knit Palm Coated Glove with Impact Pads
<b>Color:</b>	Gray Shell / Black Palm / Orange TPR
<b>Shell:</b>	Blend of High Performance Fibers and Steel
<b>Palm Coating:</b>	Sandy Nitrile
<b>Sold by:</b>	Dozen Pair
<b>Packaging (Inner Pack):</b>	12 Pairs
<b>Packaging (Case Pack):</b>	72 Pairs

**CUT PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ASTM F1790-97
<b>Test Results:</b>	4314 grams ANSI Level 5
<b>Test Method:</b>	ASTM F2992-15
<b>Test Results:</b>	4612 grams ANSI Level A7

**ABRASION PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ASTM D3884-10
<b>Test Results:</b>	ANSI Level 5, 10,904 cycles

**IMPACT PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ANSI/ISEA 138-2019
<b>Test Results:</b>	ANSI Level 1

**CE EN 388 STANDARD**

<b>EN Abrasion Resistance:</b>	§ 6.1	Level 4
<b>EN Cut Resistance:</b>	§ 6.2	Level 5
<b>EN Tear Resistance:</b>	§ 6.3	Level 4
<b>EN Puncture Resistance:</b>	§ 6.4	Level 3

**WASHING INSTRUCTIONS**

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.