

**PRODUCT SPECIFICATION SHEET****PRODUCT INFORMATION****Style:** I2469

<b>Sizing:</b>	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	Small	I2469S	Red
	Medium	I2469M	Green
	Large	I2469L	Brown
	XLarge	I2469XL	Navy Blue
	XXLarge	I2469XXL	Black

**Registered Brand Name:** FlexTech™**Classification:** Impact**PRODUCT DESCRIPTION****Description:** 15-Gauge Seamless Knit Palm Coated Glove with Impact Pads and Thumb Crotch**Color:** Hi-Viz Yellow Shell / Black Palm / Orange TPR**Shell:** Blend of High Performance and Cooling Fibers**Palm Coating:** Sandy Nitrile**Sold by:** Dozen Pair**Packaging (Inner Pack):** 6 Pairs**Packaging (Case Pack):** 72 Pairs**CUT PROTECTION PERFORMANCE INFORMATION****Test Method:** ASTM F2992-15**Test Results:** 1847 grams  
ANSI Level A4**ABRASION PROTECTION PERFORMANCE INFORMATION****Test Method:** ASTM D3884-10**Test Results:** ANSI Level 4 4518 cycles**IMPACT PROTECTION PERFORMANCE INFORMATION****Test Method:** ANSI/ISEA 138-2019**Test Results:** ANSI Level 1**CE EN 388 STANDARD****EN Abrasion Resistance:** § 6.1 Level 4**EN Cut Resistance:** § 6.2 Level 5**EN Tear Resistance:** § 6.3 Level 4**EN Puncture Resistance:** § 6.4 Level 3**WASHING INSTRUCTIONS**

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

*Wells Lamont Industrial**Toll-Free 1.800.247.3295 www.wellslamontindustrial.com*