WELLS LAMONT PRODUCT SPECIFICATION SHEET

DDODLICT INCODMATION

PRODUCT INFORMATION

Style: Y9277

Part # Size Overedge Sizing: XXSmall Y9277XXS Purple XSmall Y9277XS Yellow Small Y9277S Red Medium Y9277M Green Y9277L Brown Large

> XXLarge FlexTech™

XLarge

Registered Brand Name:FlexTech™Classification:Palm Dip

PRODUCT DESCRIPTION

Y9277XL

Y9277XXL

Navy Blue

Black

 Description:
 Seamless Knit Palm Coated Glove

 Color:
 Charcoal Gray Shell / Gray Palm

Shell: Synthetic Knit Palm Coating: Polyurethane

This Glove is Silicone Free

Sold by: Dozen Pair Packaging (Inner Pack): 12 Pairs Packaging (Case Pack): 144 Pairs

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F1790-97
Test Results: 0.44lbs. / 200 grams

ANSI Cut Level: 1

 Test Method:
 ASTM F2992-15

 Test Results:
 271 grams

 ANSI Level A1

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3389-10
Test Results: ANSI Level 4 3,072 Cycles

PUNCTURE PERFORMANCE INFORMATION

 Test Method:
 EN388:2003

 Test Results:
 40N

 ANSI Level:
 2

CE EN 388 STANDARD

EN Abrasion Resistance: § 6.1 Level 4
EN Cut Resistance: § 6.2 Level 1
EN Tear Resistance: § 6.3 Level 3
EN Puncture Resistance; § 6.4 Level 1

WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pretreat with a stain remover. Do not use bleach or dry cleaning solution.

CAUTION

This glove does not contain cut resistant materials. Do not use in conditions where cut protection is needed.

MARNING: Cancer - www.P65Warnings.ca.gov

Wells Lamont Industrial

Toll-Free 1.800.247.3295 www.wellslamontindustrial.com