

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION

Style: 1786

Sizing:	Size	Part #	Overedge Color
	XSmall	1786XS	Green
	Small	1786S	Yellow
	Medium	1786M	Blue
	Large	1786L	White
	XLarge	1786XL	Orange
	XXLarge	1786XXL	Black



Classification: Cut Resistant

PRODUCT DESCRIPTION

Description: Loop-Out Terry Cut Glove
Color: Gray
Material: Flame Resistant Fibers and Stainless Steel with Kevlar Reinforcement
Gauge: 7

Sold by: Dozen pair
Packaging (Inner Pack): 3 Pairs
Packaging (Case Pack): 36 Pairs

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F1790-97-CPPT
Test Results: 1,991 grams / 4.39 lbs
ANSI Level 4

Test Method: ASTM F2992-15
Test Results: 1877 grams
ANSI Level A4

FLAME TESTING INFORMATION

Test Method: ASTM F1358-08
Test Results: ANSI Level 2

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3884-09
Test Results: ANSI Level 3, 1771 Cycles

WASHING INSTRUCTIONS

Remove all large particles. Rinse with cold water then machine wash in warm water with mild detergent or soap for 10-15 minutes. Water temperature should not exceed 160°F (71°C). Rinse in cold water. Tumble dry for 10-15 minutes, not exceeding 150°F (67°C). Do not use bleach or dry cleaning solution.

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial
Toll-Free 1.800.247.3295 www.wellslamontindustrial.com