



## PRODUCT SPECIFICATION SHEET

### PRODUCT INFORMATION

**Style:** Cut Resistant Sleeve

**Sizing:**

| <u>Size</u> | <u>Part #</u>          |
|-------------|------------------------|
| 18"         | Standard<br>5600SLV-18 |

**Classification:** Cut Resistant



### PRODUCT DESCRIPTION

**Description:** 15g Cut Resistant Sleeve (CFR 21 - Approved for Food Contact)

**Color:** Blue

**Shell:** Combination of high performance, durable fibers and wire

**Sold by:** Dozen Pieces

**Packaging (Inner Pack):** 6 Pieces

**Packaging (Case Pack):** 48 Pieces

### CUT PROTECTION PERFORMANCE INFORMATION

**Test Method:** ASTM F2992-15

**Test Results:** 4,678 grams

**ANSI Level:** A7

### ABRASION PROTECTION PERFORMANCE INFORMATION

**Test Method:** ASTM D3884-09

**Test Results:** ANSI Level 2, 774 Cycles

### PUNCTURE PERFORMANCE INFORMATION

**Test Method:** EN388:2003

**Test Results:** 64N

**ANSI Level:** 3

### WASHING INSTRUCTIONS

Remove all large particles. Rinse with cold water then machine wash in warm water with mild detergent or soap for 10-15 minutes. Water temperature should not exceed 160°F (71°C). Rinse in cold water. Tumble dry for 10-15 minutes, not exceeding 150°F (67°C). A diluted bleach solution may be used (5.25% sodium hypochlorite or 1:10 household bleach).

### CAUTION

Sleeves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial  
Toll-Free 1.800.247.3295 [www.wellslamontindustrial.com](http://www.wellslamontindustrial.com)